

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An enclosure assembly for a fingerprint sensor, the enclosure assembly comprising:

a stationary member including at least two substantially parallel sidewalls, the sidewalls partially defining a cavity in which the fingerprint sensor is disposed;

a moveable access piece, which has a surface area larger than the surface area of the fingerprint sensor, the moveable access piece having a conductive portion electrically coupled to ground, wherein the moveable access piece is configured to move relative to the stationary member; and

a fingertip contour area located on a forward portion of the access piece, the finger contour area having a rounded, cup-shaped upper region configured to receive thereon a rounded tip portion of a fingertip; and

a movement apparatus configured to maintain the moveable access piece in a position covering the fingerprint sensor and yet to allow motion of the moveable access piece relative to the stationary member so as to expose the fingerprint sensor.

2. (Original) The enclosure assembly of claim 1, wherein the movement apparatus comprises a spring to engage the moveable access piece and the stationary member, the spring configured to apply sufficient pressure to the moveable access piece so as to generally maintain the moveable access piece in the position covering the fingerprint sensor.

3. (Original) The enclosure assembly of claim 2, further comprising an image quality indicator means communicatively coupled to the fingerprint sensor, the image quality indicator configured to signal whether biometric information collected by the fingerprint sensor is acceptable.

4. (Withdrawn)

5. (Original) The enclosure assembly of claim 1, further comprising a switch configured to electrically couple a power supply to the fingerprint sensor after the moveable access piece exposes at least a portion of the cavity.

6. (Original) The enclosure assembly of claim 1, wherein the moveable access piece has a first end and a second end, the first end having a concave surface portion configured to receive a fingertip;

7. (Withdrawn)

8. (Original) An enclosure assembly for a fingerprint sensor, the enclosure assembly comprising:

a stationary member including at least two substantially parallel sidewalls, the sidewalls partially defining a cavity in which the fingerprint sensor is disposed;

a moveable access piece, which has a surface area larger than the surface area of the fingerprint sensor, the moveable access piece having a conductive portion electrically coupled to ground, wherein the moveable access piece is configured to move relative to the stationary member;

a movement apparatus configured to maintain the moveable access piece in a position covering the fingerprint sensor and yet to allow motion of the moveable access piece relative to the stationary member so as to expose the fingerprint sensor; and

a switch configured to electrically couple a power supply to the fingerprint sensor after the moveable access piece exposes at least a portion of the cavity.

9. (Original) The enclosure assembly of claim 8, wherein the movement apparatus comprises a spring to engage the moveable access piece and the stationary member,

the spring configured to apply sufficient pressure to the moveable access piece so as to generally maintain the moveable access piece in the position covering the fingerprint sensor.

10. (Withdrawn)

11. (Original) The enclosure assembly of claim 8, further comprising an image quality indicator means communicatively coupled to the fingerprint sensor, the image quality indicator configured to signal whether biometric information collected by the fingerprint sensor is acceptable.

12-20. (Withdrawn)

21. (New) The enclosure assembly of claim 1 wherein the fingertip contour area is positioned in a location to align the core of the fingerprint with the sensor when the access piece is moved to an open position.

22. (New) An enclosure assembly for a fingerprint sensor, the enclosure assembly comprising:

a stationary member having a fingerprint sensor disposed thereon;

a movable access piece, the movable access piece having a surface area which is larger than the surface area of the fingerprint sensor, the movable access piece having a fingertip contour area located on a forward portion thereof, the fingertip contour area having a rounded, cup-shaped upper region configured to receive thereon a rounded tip portion of a fingertip and positioned to align the core of the fingerprint on the finger adjacent the fingerprint sensor when the fingertip is positioned in the contour area in the open condition; and

a movement apparatus configured to maintain the movable access piece in a position covering the fingerprint sensor and allowing motion of the movable access piece relative to the stationary member so as to expose the fingerprint sensor when the fingertip is positioned on the movable access piece and moves it to an open position.

23. (New) The enclosure assembly according to claim 22 wherein said movement apparatus includes a spring connected to the movable access piece, the spring being coupled to a rear wall portion of the movable access piece and aligned in the same plane as the movable access piece so as to apply direct force to the movable access piece in the same line of force as movement of the movable access piece.

24. (New) The enclosure apparatus according to claim 22, further including an activation switch positioned adjacent to the movable access piece, the activation switch causing the sensing circuit to be enabled upon tripping of the activation switch, the activation switch being stationary relative to the movable member.